



Lite Series “All-In-One System”

OVERVIEW

Surveillus Networks Lite Series video management systems make it easy to record, manage and share all your digital surveillance information. Designed specifically for mission critical applications, we paired our intuitive interface with powerful search capabilities, while maintaining ease of use. These features ensure that Surveillus Lite not only meets but exceeds the most demanding requirements in the surveillance industry. The Surveillus Review™ client redefines digital video retrieval with its strong focus on usability, powerful and easy-to-use search functions, bookmarks, storyboard exports, and much more. The Surveillus Monitor app allows users to seamlessly control managed monitors from any system decoder connected to the VMS. The Surveillus Commander™ browser-based app streamlines your configuration process and provides system health monitoring. Install additional storage, expand your camera base, and add or delete users with ease. Real-time event monitoring is also included with each Surveillus Networks VMS.

FEATURES

- All-In-One video management system
- Intuitive user interface for live viewing, playback and investigations
- Hardware, storage and video management software combined for ease of installation
- Browser based configuration, management and health monitoring
- Simple camera discovery and configuration
- Storyboard Exports
- Easily export multiple hours of video
- Synchronized playback
- Bookmarks for event logging
- RAID-5 redundant storage
- Camera history graph with events
- Slow Motion playback in addition to FF/RW
- View up to 12 streams @ 30 FPS/1080P
- Standard retention-based, scheduled or event-based grooming
- Data pruning
- Programmable user permissions
- Customizable layouts
- Digital PTZ
- Real-time event monitoring
- Monitor wall controls

Max Video Storage Rate (Mbps)	240 Mbps
Operating System	Windows 10 Pro 64 Bit
CPU	Intel Core i7-6700
Memory	32GB DDR4-2666MHz RAM
OS Drive	240GB SSD
Storage Drive Bays	4 - Hot-swap 3.5" SATA3 drive bays
Video / Display	Intel - Single display for video * Optional Decoders can be utilized for additional displays as needed.
Audio	RealTek ALC 888S HD Audio
Network Interface	2 - RJ45 Gigabit Ethernet LAN ports, 1 - RJ45 Dedicated IPMI LAN port
Operating Temperature:	10°C to 35°C (50°F to 95°F)
Keyboard and Mouse	Not Included
Monitor	Not Included
Dimensions	H 1.7" (43mm) W 17.2" (437mm) D 19.85" (503mm)
Weight	Gross Weight: 30.4 lbs (13.8 kg) Net Weight: 17.6 lbs (8 kg)
Power Supply	350W AC power supply w/ PFC
Input Voltage	100-240 V, 50-60 Hz,
Rated Input Current	4.2A (100V) to 1.8A (240V)
Consumption	1,494 BTUs/hour (Worst Case)
Warranty Period	Specific models include 3 years of support for bundled channels included

Models	Cameras Licenses Included
SURLT1-16xx	16
SURLT1-32xx	32

* RAID 5 reduces net usable storage for each system by 1 of the selected drive sizes.
 * Standard US power cords provided. Additional cords available upon request.
 * xx indicates quantity and size of HDDs provided with each model.

Accessories

SURDECXE	HD Decoder for additional displays and monitor wall functionality
-----------------	---